Application No.: 10/717,544 Docket No.: SON-2869

(80001-2869)

## **AMENDMENTS TO THE CLAIMS**

Please cancel claims 5-8 and 13-16 and amend claims 4 and 12 as set forth below.

1. (PREVIOUSLY PRESENTED) An amplifier apparatus, which is switched from a non-readout state to a readout state based on a control signal, for reading out a signal containing a servo signal by signal readout means, amplifying the signal by an amplifier, and outputting said amplified signal, wherein

said amplifier apparatus comprises filtering means for allowing a high frequency part of a signal to pass through, thereby filtering said signal, said filtering means having a first cutoff frequency during a first prescribed time period after said readout state is initiated, a second cutoff frequency that is lower than said first cutoff frequency during a second prescribed time period after said first prescribed time period has passed, and a third cutoff frequency that is lower than said second cutoff frequency after said second prescribed time period has passed.

- 2. (ORIGINAL) The amplifier apparatus of Claim 1, wherein said second prescribed time period is shorter than a readout time for said servo signal contained in said signal.
- 3. (ORIGINAL) The amplifier apparatus of Claim 1 or Claim 2, wherein said filtering means for allowing said high frequency part of said signal to pass through is a high pass filter, and said high pass filter is placed between a first amplifier and a second amplifier, which are for amplifying said signal.
- 4. (CURRENTLY AMENDED) An amplifier apparatus, which is switched from a non-readout state to a readout state based on a control signal, for reading out a signal containing a servo signal by signal readout means, amplifying said signal by an amplifier, and outputting said amplified signal, wherein said an amplifier apparatus comprises:

variable filtering means with a plurality of cutoff frequencies,

- a first amplifier, and
- a second amplifier; and

switching means for controlling said amplified signal output, and said switching means being placed on an output side of said second amplifier,

Application No.: 10/717,544 Docket No.: SON-2869

(80001-2869)

wherein said output signal from said first amplifier passes through said variable filtering means and is amplified by said second amplifier.

wherein said variable filtering means has a first cutoff frequency, a second cutoff frequency, and a third cutoff frequency,

wherein after said non-readout state is switched to said readout state, said variable filtering means has said first cutoff frequency during a first prescribed time period,

wherein said switching means is turned on, and said variable filtering means has said second cutoff frequency during a second prescribed time period after said first prescribed time period has passed,

wherein said variable filtering means has a third cutoff frequency after said second prescribed time period has passed, and

wherein said first cutoff frequency is higher than said second cutoff frequency and said second cutoff frequency is higher than said third cutoff frequency.

Claims 5-8 are (CANCELED).

9. (PREVIOUSLY PRESENTED) A magnetic recording and reproducing apparatus comprising an amplifier apparatus, which is switched from a recording state to a readout state based on a control signal, for reading out a signal containing a servo signal by signal readout means, amplifying said signal by an amplifier, and outputting said amplified signal, wherein:

said amplifier apparatus comprises filtering means for allowing a high frequency part of a signal to pass through, thereby filtering said signal, said filtering means having a first cutoff frequency during a prescribed time period after said readout state is initiated, a second cutoff frequency that is lower than said first cutoff frequency during a second prescribed time period after said first prescribed time has passed, and a third cutoff frequency that is lower than said second cutoff frequency after said second prescribed time period has passed.

10. (PREVIOUSLY PRESENTED) The magnetic recording and reproducing apparatus comprising the amplifier apparatus of Claim 9, wherein said second prescribed time period is shorter than a readout time for said servo signal, which is contained in said signal.

Application No.: 10/717,544 Docket No.: SON-2869

(80001-2869)

11. (ORIGINAL) The magnetic recording and reproducing apparatus comprising the amplifier apparatus of Claim 9 or Claim 10, wherein said filtering means for allowing a high frequency part of a signal to pass through is a high pass filter, and said high pass filter is placed between a first amplifier and a second amplifier, which amplify said signal.

12. (CURRENTLY AMENDED) A magnetic recording and reproducing apparatus comprising an amplifier apparatus, which is switched from a non-readout state to a readout state based on a control signal, for reading out a signal containing a servo signal by signal readout means, amplifying said signal by an amplifier, and outputting said amplified signal, wherein

said magnetic recording and reproducing apparatus comprising an amplifier apparatus comprises variable filtering means with a plurality of cutoff frequencies, a first amplifier, and a second amplifier; wherein

an output signal from said first amplifier passes through said variable filtering means and is amplified by said second amplifier,

wherein switching means for controlling an amplified signal output is placed on an output side of said second amplifier,

wherein said variable filtering means has a first cutoff frequency, a second cutoff frequency, and a third cutoff frequency,

wherein after said non-readout state is switched to said readout state, said variable filtering means has said first cutoff frequency during a first prescribed time period,

wherein after said first prescribed time period has passed, said switching means is turned on, and said variable filtering means has said second cutoff frequency during a second prescribed time period,

wherein said variable filtering means has a third cutoff frequency after said second prescribed time period; and

wherein said first cutoff frequency is higher than said second cutoff frequency, and said second cutoff frequency is higher than said third cutoff frequency.

Claims 13-16 are (CANCELED).